

# RAISED ACCESS FLOORING



CEMENTITIOUS RAISED ACCESS FLOOR - HPL FINISHED (FS800)





### CEMENTITIOUS RAISED ACCESS FLOOR - HPL FINISHED (FS800)

Description	:	Steel Structure, Top & Bottom Steel Plate welded (Bao Steel), Cement Infilled, Top High Pressure Laminated (1.0 mm Antistatic) Finished.
Panel Size	:	600 x 600 mm
Fire Performance	:	Class A1
Panel Thickness	:	35 mm
Panel Weight	:	13.5 Kg

### PEDESTAL & STRINGER

Flat Pedestal	:	Flat Steel Top 75 x 75 x 3.0mm, Full Threaded rod, Base Plate: 95 x 95 x 2.0mm
Stringer	:	Galvanized Steel Tube - 32 x 21 x 570 x 1.0mm)

### SPECIFICATION

Concentrated Load	:	$\geq 356$ Kg
Uniform Load	:	$\geq 16100$ N/m <sup>2</sup>
Ultimate Load	:	$\geq 10680$ N
Impact Load	:	$\geq 536$ N
Rolling Load	:	10 Times - 3560 N 1000 Times - 2670 N

**GENERAL ASSEMBLY**



**GRID ASSEMBLY**

